

手動壓膜機

c sun

MANUAL TYPE LAMINATOR

CSL-M25R/E



Leading in Thermal and UV Light Processing Equipment



CSL-M25R/E

<p>適用範圍 Panel Dimension</p>	<p>Length: 250 to 640mm (10" to 25")</p> <p>Width: 250 to 640mm (10" to 25")</p> <p>Thickness: 0.05mm (without copper) to 3.2mm (0.002-0.12")</p>
<p>乾膜尺寸 Dry film dimension</p>	<p>Width: 250 to 610mm (10" to 24")</p> <p>Thickness: 15 to 76μm (0.6 to 3.0mil)</p> <p>Supply roll diameter: ϕ160-250mm Max. (Optional: 1000ft)</p>
<p>壓膜製程 Lamination process</p>	<p>Conveyor speed: 1-4 m/min (39.37 - 157.48in/min) adjustable</p> <p>Pressure: 2-5kg/cm²(40-70psi)</p> <p>Pressure roll size: ϕ78.6 x 760mm</p>
<p>加熱方式 Heating method</p>	<p>CSL-M25R: Cartridge heater 2.0KW x 2</p> <p>CSL-M25E: Induction heater 1.5KW x 2</p>
<p>外部供應 Utilities</p>	<p>Air supply: Compressed air@6kgf/cm²(90psi), 2L/min</p> <p>Power: AC220V 1ϕ60Hz (various power supply choices available)</p>
<p>機台尺寸 Dimension</p>	<p>External dimensions: L1190 x W775 x H1235mm (不含下座 without base table)</p> <p>L1190 x W775 x H1740mm (含下座 with base table)</p>
<p>排氣 Exhaust</p>	<p>ϕ4" x 1 (4CMM)</p>

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
受長期研發需要，本公司保有規格修改之權利，恕不另行通知

DM201605-0000