

紫外線雙面照射機

3D UV CURING MACHINE

UVC-1014+1023ISCF



特點

- 低溫：照射溫度 $\leq 48^{\circ}\text{C}$
- 節能：以鍍膜石英玻璃+新型氣冷方式不需冰水機就可以達到低溫效果
- 產能：800-1,000雙/小時
- 雙面照射

ADVANTAGE

- Low temperature : Irradiation temperature $\leq 48^{\circ}\text{C}$
- Energy saving: The coated quartz glass + new air cooling method can achieve low temperature effect without the need of ice chiller machine
- Capacity: 800-1,000 pairs / hour
- 3D UV irradiation with top and bottom





紫外線雙面照射機
3D UV CURING MACHINE

UVC-1014+1023ISCF

尺寸 Exterior Dimensions (L/W/H mm)	有效輸送寬 Effective Width	輸送速度 Conveyor Speed	電力 Power
3200 x 1020 x 2550	380 m/m	3~12m/min	24 KVA

Due to C SUN continuing efforts to improve their systems, these specifications are subject to change without notice.
因應長期研發需要，本公司保有規格修改之權利，恕不另行通知

應用

- 將UV處理劑擦拭於鞋材上，經UV照射乾燥後使鞋材極性增加 變得容易黏著

新增功能

- 燈管無法正常點燈時，立即警報並顯示燈管故障
- 未依標準程序點燈時，檢知警示
- UV系統故障時，警示燈閃爍並停止輸送帶動作

APPLICATION RESULTS

- Apply the UV primer on the midsole's top and bottom, after UV dried, became easy stick into.

NEW FEATURE

- When UV lamp are not lighting normally, will display lamp failure and alarm immediately.
- When not follow the standard procedures when lighting, will detect and alerts.
- When UV system are failure, warning light will on and stop the conveyor moving completed.

DM202001-000

業務洽詢專線： +86-139-26269713 (華南) +86-139-26260250 (華東) +886-935-227109 (臺灣)

jung@csun.com.tw

台北

新北市林口區工二工業區
工八路2-1號
TEL:886-2-26017706
FAX:886-2-26018854

台中

台中市南屯區
精科二路11號
TEL:886-4-23591651
FAX:886-4-23592678

廣州

廣州市花都區獅嶺鎮
利和路6號
TEL:86-20-86846341-3
FAX:86-20-86910139

東莞

東莞市大朗鎮長塘第三工業區78號
松湖雲谷雲松樓1樓
TEL:86-769-85331146
FAX:86-769-85331145

昆山

江蘇省昆山市高新區(玉山鎮)
恒盛路1369號
TEL:86-512-57780230
FAX:86-512-57780229