

精密熱風烤箱

c sun

CABINET OVEN FOR PCB



MOL-8WS

雙獨立控制無塵烤箱
Two Independent Clean Cabinet Oven

SCMO-8WS

雙獨立控制台車烤箱
Two Independent Cart Oven



SMO-7A/8A

垂直送風烤箱
Vertical Airflow Oven



www.csun.com.tw

Leading in Thermal and UV Light Processing Equipment

CABINET OVEN 規格表

型號 Model	SMO-7A	SMO-8A	SCMO-8WS
內尺寸 Internal Dimension W x D x H (mm)	1360 x 850 x 1280	1360 x 1050 x 1280	840 x 710 x 1530 (兩箱)
外尺寸 External Dimension W x D x H (mm)	2200 x 1083 x 2543 (含桿式指示燈)	2200 x 1283 x 2592 (含桿式指示燈)	2700 x 940 x 2563 (含桿式指示燈與搬運輸)
均勻度 Uniformity	±1.5°C, 75°C(有載)(Loaded) ±1.5%, 150°C(有載)(Loaded)	±1.5°C, 75°C(有載)(Loaded) ±1.5%, 150°C(有載)(Loaded)	±2%, 150°C(空載)(Unloaded)
送風方式 Air Circulation	垂直送風 Vertical air flow	垂直送風 Vertical air flow	水平送風 Horizontal flow

板彎壓平機規格表

型號 Model	HAF-5
內尺寸 Internal Dimension W x D x H (mm)	900 x 770 x 1100
外尺寸 External Dimension W x D x H (mm)	1485 x 1080 x 2400
壓板區 Heating zone	3個加熱區 (3 heating zones) 每層高度160mm (Height of each zone) 推板高Max:130mm(PCB Stack Height) 有效壓板區 570×685mm (Effective Heating Zone)

HAF-5
板彎壓平機
Dewarping Machine



自動沖孔預熱機規格表

型號 Model	PPO-2	PPO-3
外尺寸 Exterior Dimension W x D x H (mm)	1173 x 886 x 1602	1162 x 987 x 1622
適用尺寸 Panel Dimension W x D (mm)	Min: 100 x 380 Max: 400 x 600	Min: 100 x 380 Max: 500 x 600
同時加熱片數 Processing capacity	18 pcs	
適用溫度範圍 Temperature Range	50°C~120°C	
排出速度 Out-feeding speed	4.5~30 seconds (可調整)	
板堆積量 Top plate In-feeding	150 pcs (1.6mm Panel)	
控制系統 Control system	PLC Control	



PPO-2/3
自動沖孔預熱機
Preheat Oven

DM202008-500-QS

bearhuang@csun.com.tw (臺灣) ching@csun.com.tw (華南) omarshuang@csun.com.tw (華東)

台北
新北市林口區工二工業區
工八路2-1號
TEL:886-2-26017706
FAX:886-2-26018854

台中
台中市南屯區
精科二路11號
TEL:886-4-23591651
FAX:886-4-23592678

廣州
廣州市花都區獅嶺鎮
利和路6號
TEL:86-20-86846341-3
FAX:86-20-86910139

東莞
東莞市大朗鎮長塘第三工業區78號
松湖雲谷雲松樓1樓
TEL:86-769-85331146
FAX:86-769-85331145

昆山
江蘇省昆山市高新區(玉山鎮)
恒盛路1369號
TEL:86-512-57780230
FAX:86-512-57780229