

EVO LL III 5W30

SYNTHETIC HIGH END MOTOR OIL

DESCRIPTION

Syntix EVO is a full synthetic engine oil of the latest generation, formulated using a combination of high-quality base oil and optimized additives. The product meets the highest standards for petrol and diesel engines and offers additional protection because of its exceptional viscosity index.

PROPERTIES

- Improves fuel efficiency
- Provides safe lubrication at extreme temperatures
- Offers reliable protection against friction and wear
- Extends oil drain intervals
- Improves cold start performance
- Offers resistance to shearing
- Maintains a high and stable viscosity index
- LOW SAPS technology compatible with DPF

APPLICATION

Suitable for turbocharged and non-turbocharged petrol and diesel engines. Specifically designed to optimize performance of VW-Group engines with VW 504.00/507.00 specifications. Compatible with particulate filters thanks to LOW SAPS technology.

TYPICALS

Density at 15 °C	0,851 kg/l
Viscosity at -25 °C	5950 mPa.s
Viscosity at 40 °C	69,20 mm ² /s
Viscosity at 100 °C	12,00 mm ² /s
Viscosity index	171
Flash point COC	230 °C
Pour Point	-42 °C
Total base number	6,7 mgKOH/g

SPECIFICATIONS

ACEA C2 / C3
API SN
BMW LL04
MB 229.51
PORSCHEC30
VW 504.00/507.00
FIAT 9.55535-S1
GM DEXOS 2

PACKAGING

1L bottle (12 x 1L/box)
4L bottle (4 x 4L/box)
5L bottle (4 x 5L/box)
20L, 60L, 200L drum

