

PS-333 PPM Oxygen Sensor is a galvanic type micro fuel cell specific to oxygen. Its innovative design with electro-etched sensing cathode provides an extremely smooth sensing surface for excellent signal stability, very low noise and drift. Proprietary electrolyte formulation enhances sensor performance at extreme ends of recommended operating temperature range. The sensor was designed and developed in the USA and is manufactured in Taiwan.



PS-333 Replaces: AII GPR-12-333 : AST SRX-MA333

Specifications*

Sensor Technology	Galvanic Type Micro Fuel Cell
Measuring Range	0.1 to 10,000 PPM
Signal Output ¹	420-780 uA
Response Time T90	7 seconds
Accuracy ²	+/- 1% of signal
Drift ²	< 2%
Linearity	+/- 1%
Repeatability	+/- 0.5%
Temperature Coefficient	-2.0% / °C
Operating Temperature	0 to 45°C
Storage Temperature	0 to 45°C
Recommended Flow Rate	0.5 - 5 SCFH
Humidity Non-Condensing	0 - 99% RH
Expected Life ³	18 months
Recommended Storage	6 months
Warranty ⁴	12 months
PCB Connections	Center Negative Outer Positive

Note: PS-333 is packaged in a metalized bag under nitrogen which is then placed in 4" x 3" x 2" box. Use sensor immediately after removing from the sealed bag. After removing, do not leave sensor in air for an extended period. Doing so may have a negative impact on its performance and operating life.

1. Signal Output measured in air at 25°C and at atmospheric pressure.
2. At constant temperature and pressure.
3. At operating temperature less than 35°C, atmospheric pressure and oxygen content in sample gas less than 10,000 ppm.
4. AUT warrants the sensor to be free from defects in materials and workmanship. AUT will not be held liable for sensor damaged due to customer neglect and misuse.

* Specifications are validated during design and are subject to change without notice.