






Mechanical Specifications

Parameter	Specifications	Unit	Remark
Screen Size	11.6	Inch	
Display Resolution	640(H)×960(V)	Pixel	Dpi:100
Active Area	244.512(H)×163.008(V)	mm	
Pixel Pitch	0.2547×0.2547	mm	
Pixel Configuration	Rectangle		
Outline Dimension	254.31(H)×176.35(V) ×0.9 (D)	mm	Without masking film
Weight	73.0±0.5	g	

ABSOLUTE MAXIMUM RATING

Table 10-1: Maximum Ratings

Symbol	Parameter	Rating	Unit	Humidity	Unit	Note
V _{CI}	Logic supply voltage	-0.5 to +6.0	V	-	-	
T _{OPR}	Operation temperature range	0 to 30	°C	45 to70	%	Note 10-1
T _{ttg}	Transportation temperature range	-25 to 60	°C	-	-	Note 10-2
T _{stg}	Storage condition	0 to 30	°C	45 to70	%	Maximum storage time: 5 years
-	After opening the package	0 to 30	°C	45 to70	%	

Power Consumption

Parameter	Symbol	Conditions	TYP	Max	Unit	Remark
Panel power consumption during update	-	25°C	-	600	mAs	-
Deep sleep mode	-	25°C	-	5	uA	-

Mas=update average current × update time

Input/Output Terminals

Pin #	Single	Description	Remark
1	NC	No connection and do not connect with other NC pins	Keep Open
2	GDR	N-Channel MOSFET Gate Drive Control	
3	RESE	Current Sense Input for the Control Loop	
4	NC	No connection and do not connect with other NC pins e	Keep Open
5	VSH2	Positive Source driving voltage	
6	TSCL	I2C Interface to digital temperature sensor Clock pin	Note 6-6
7	TSDA	I2C Interface to digital temperature sensor Date pin	Note 6-6
8	BS1	Bus selection pin	Note 6-5
9	BUSY	Busy state output pin	Note 6-4
10	RES #	Reset	Note 6-3
11	D/C #	Data /Command control pin	Note 6-2
12	CS #	Chip Select input pin	Note 6-1
13	SCL	serial clock pin (SPI)	
14	SDA	serial data pin (SPI)	
15	VDDIO	Power for interface logic pins	
16	VCI	Power Supply pin for the chip	
17	VSS	Ground	
18	VDD	Core logic power pin	
19	VPP	Power Supply for OTP Programming	
20	VSH1	Positive Source driving voltage	
21	VGH	Power Supply pin for Positive Gate driving voltage and VSH	
22	VSL	Negative Source driving voltage	
23	VGL	Power Supply pin for Negative Gate driving voltage, VCOM and VSL	
24	VCOM	VCOM driving voltage	